

# AquaLink® Touch™ Quick Review Card

The AquaLink Touch controller can easily control your backyard environment four different ways. 1) From the Home screen, by pressing your personalized Quick Action icons, 2) By selecting OTHER DEVICES and manually activating any piece of equipment, 3) Scheduling the equipment to automatically turn on and off at specific times by pressing MENU then SCHEDULE, or 4) By selecting one of the six OneTouch™ Macro buttons that turn on multiple items with the push of one button.

## Home Screen

Displays current air, pool and spa water temperatures, and your 7 personalized Quick Action icons. Spa or pool temperatures are displayed depending on which body of water is being circulated.

## Menu Button

Access all AquaLink Touch features from Menu screen including equipment schedules, system setup, AquaLink Touch settings, temperatures, password protection and more.

## Navigation Button Bar

User-friendly icons provide quick links to Home, Menu, preset OneTouch buttons, and Help information. Use Back to return to previous screen, Status to view list of equipment in use. Select Photos to access slideshow features. Turn controller off with Power button.



## Signal & Battery Status

A clear indicator of your wireless reception and battery life. The day and time is conveniently displayed.

Note: Battery life and signal strength shown on wireless models only.

## OneTouch Macros

Put the most popular features right at your fingertips. Program these "quick links" to activate your favorite features like spa jets or yard lights with the touch of a button.

## Device Control

Effortlessly manage up to 32 peripherals such as heaters, lights, pumps, solar, or pool cleaners.

The AquaLink Touch owner's manuals may be downloaded online at [www.jandy.com](http://www.jandy.com)

To Contact Technical Support:  
P: 800.822.7933 | F: 800.479.8324  
[techsupport.vista@zmp-zodiac.com](mailto:techsupport.vista@zmp-zodiac.com)

# AquaLink® Touch™

# AquaLink™ Touch™ Programming & System Defaults



## WARNING

FOR YOUR SAFETY - To Avoid property damage, injury, or death, be sure to read the Safety Warnings and Important Safety Instructions in the AquaLink Touch Owner's Manual.

**BASIC PROGRAMMING:** To set a particular piece of equipment to turn on and off at a predetermined time, touch the MENU button to display the MENU screen. From the MENU screen, select SCHEDULE to display SCHEDULE screen. To add equipment to a schedule, press NEW>SCHEDULE DEVICE. Select equipment you want to program from list, then press SELECT to return to SCHEDULE screen. The SCHEDULE screen displays programmed equipment, on/off times, and days of the week scheduled. To set/change program, touch circuit (equipment) name, select on/off times, day/weekdays/weekends and press SAVE to save changes. Repeat this process for each piece of equipment that you wish to program. You may enter an unlimited amount of scheduled programs for each piece of equipment.

**SET DATE/TIME:** Touch MENU>SET DATE/TIME. Press DATE or TIME field to select. Use keypad to change DATE or TIME, press ENTER to save changes. Use Navigation bar buttons to exit/select next task.

**LABEL AUXILIARY FUNCTIONS:** Touch MENU>SYSTEM SETUP>LABEL AUX. Select the AUX from list to label. Touch GENERAL, LIGHT or WATERFALL buttons to select common labels, or create your own CUSTOM label. Repeat for all auxiliary features.

Note 1: The labels "AIR BLOWER" and "FILL LINE" are 30 minute timed cycles.

Note 2: If DIP switches 1, 2, or 3 are on, Auxiliaries 1, 2 and 3 are labeled CLEANER, LOW SPEED and SPILLOVER (pool/spa combo systems only) cannot be relabeled.

**SET TEMPERATURE:** Touch MENU>SET TEMP. Select POOL HEAT or SPA HEAT button, use keypad to enter temperature and press ENTER to save changes. Use Navigation bar buttons to exit/select next task.

### Default Temperature Settings

Default Pool Temp.	80°F
Default Spa Temp.	102°F
Default Temp. 1*	80°F
Default Temp. 2*	60°F
*Pool only / Spa only systems	

### Default OneTouch Settings

Btn 1 - SPA MODE      Btn 2 - CLEAN MODE  
Btn 3 - ALL OFF  
Btn 4-6 - NOT ASSIGNED  
You can reprogram/add settings to TOUCH buttons under MENU > SYSTEM SETUP > TOUCH SETUP.

### Default Freeze Protection Settings

Filter Pump: Freeze Protection ON.  
All other Equipment: Freeze Protection OFF.  
NOTE: If you selected Spa to be freeze protected, water circulation will switch between pool and spa every 30 minutes during freezing conditions once freeze mode is active.